

Door Camera / Doorlock



Front Door Camera


KC-MC30 Color
KC-MC32 Color
KC-MB30 B/W

- Manual camera angle adjustment
- Protect from pollution & weather proof Material (A/L)
- Night automatic illumination (White LED and IR LED On / Built-in Camera)
- Door lock connectable.


Specifications

- Power : 12V ± 1V (power from monitor)
- Power consumption : Max. 3W
- Wiring : KC-MC30, KC-MB30 - 4 Wire, KC-MC32 - 2 Wire
- Camera angle : 120° (Angle Adjustable)
- Body material: Metal A/L
- Min. illumination : 0.1 lux (LED ON)
- Mount type : Surface mount
- Dimension(mm): 110(W) × 158(H) × 39(D)
- Monitor Connection:
 - KC-MC30 : KCV-A374, KCV-301, KCV-802R, KCV-D802R, KCV-801R, KCV-D801R, KCV-801, KCV-D801
 - KC-MC32 : KCV-A372, KCV-D372, KCV-352, KCV-D352
 - KC-MB30 : KVM-301, KVM-D301

Wiring Diagram



Dimension




Option


Specifications

- Power : DC 12V ± 1V (power from monitor)
- Power consumption : Max. 2.5W
- Wiring : KC-C63(B/W), KC-C60(Color), KC-B61(B/W) : 4 Wire, KC-C62(Color) - 2 Wire
- Mount type : Surface mount
- Camera angle : 120° (Fixed)
- Body material : Plastic
- Min. illumination : 0.1 lux (LED On)
- Mount type : Surface mount
- Dimension(mm): 95(W) × 127(H) × 34(D)
- Monitor Connection:
 - KC-C60 : KCV-J351, KCV-A374, KCV-W354, KCV-DW354, KIV-212, KIV-D212, KCV-A374, KCV-301, KCV-802R, KCV-D802R, KCV-801R, KCV-D801R, KCV-W354, KCV-DW354
 - KC-C62 : KCV-A372, KCV-D372, KCV-352, KCV-D352
 - KC-B61 : KIV-102, KIV-D102, KVM-520, KVM-D520, KVM-301, KVM-604
 - KC-C63 : KIV-102, KIV-D102

Wiring Diagram



Dimension



Option



Front Door Camera

KC-C60/C62 Color
KC-B61/C63 B/W

- Night automatic illumination (White LED and IR LED On / Built-in Camera)
- Door lock connectable



Front Door Camera


KC-C71 Color

- Manual camera angle adjustment
- Night automatic illumination (White LED On / Built-in Camera)


Specifications

- Power : 12V ± 1V (power from monitor)
- Power consumption : Max. 2.5W
- Wiring : 4 Wire
- Lens : F : 2.0, f = 3.6mm
- Camera angle : 120° (Angle Adjustable)
- Body material: Plastic
- Min. illumination : 0.1 lux (LED ON)
- Mount type : Flush mount
- Dimension(mm) : 89(W) × 131(H) × 13(D)
- Box Size (mm) : 125(W) × 161(H) × 17(D)
- Monitor Connection: KHN-970, KHN-971, KHN-973, KHN-880, KHN-881, KHN-883, KHN-870, KHN-871, KHN-873, KHV-478, KHV-458, KCV-358, KCV-J351, KCV-C374

Wiring Diagram




Dimension




Specifications

- Power : 12V ± 1V (power from monitor)
- Power consumption : Max. 2.5W
- Wiring : 4 Wire
- Camera angle: 90° (Fixed)
- Body material: Metal
- Min. illumination: 0.1 lux (LED ON)
- Mount type : Surface mount
- Assurance temperature : -20°C ~ +50°C
- Dimension (mm) : 110 (W) x 158(H) x 39(D)
- Monitor Connection :
 - KC-MC31: KCV-A374, KCV-301, KCV-802R, KCV-D802R, KCV-801R, KCV-D801R, KCV-W354, KCV-DW354
 - KC-MB31: KVM-301, KVM-D301

Wiring Diagram



Dimension



Front Door Camera

KC-MC31 Color
KC-MB31 B/W

- Protect from pollution & weather proof Material (A/L)
- Night automatic illumination (White LED On / Built-in Camera)
- Door lock connectable.